

MATERIAL SAFETY DATA SHEET

SECTION 1 - SOURCE/IDENTITY/USE INFORMATION

MANUFACTURER	SUPPLIER
GC AMERICA INC.	
3737 West 127th St.	
Alsip, Illinois, 60803	
Telephone: 708-597-0900	
Hours: Mon.- Fri. 8:00 am. - 5:00 pm. C.S.T.	
Transportation Emergency Telephone No. 800-424-9300	

COMMON NAME: FUJI II LIQUID
FUJI II CAPSULES LIQUID

Chemical Name: N.A.

PRODUCT USE: Dental composite filling material - liquid component

The following information is provided with regard to the toxicity and hazards of the pure components present in this portion of the unmixed powder/liquid system.

SECTION 2 - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

COMPONENT AND C.A.S.	EXPOSURE LIMITS	LD50/LC50	%
Polyacrylic acid (not listed)	TWA=10ppm (ACGIH)	LD50 = 2500mg/kg (oral rat) LC50=N.E.	40-50%

SECTION 3 - PHYSICAL/CHEMICAL PROPERTIES

BOILING POINT: 101°C	SPECIFIC GRAVITY (H ₂ O = 1): 1.18
VAPOR PRESSURE: N.E.	MELTING POINT: 13°C
VAPOR DENSITY: N.E.	EVAPORATION RATE: N.E.
SOLUBILITY IN WATER: N.E.	ODOR THRESHOLD: N.E.
COEFFICIENT OF OIL/WATER DISTRIBUTION: N.E.	

APPEARANCE AND ODOR: Colorless, slightly viscous and odorless liquid

SECTION 4 - FIRE AND EXPLOSION DATA

FLASH POINT: Not flammable FLAMMABLE LIMITS: N.A.

EXTINGUISHING MEDIA: Alcohol foam

SPECIAL FIRE FIGHTING PROCEDURES: Full protective clothing and self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None

HAZARDOUS COMBUSTION PRODUCTS: Emits Acrid smoke when heated beyond boiling point.

SECTION 5 - REACTIVITY DATA

STABILITY:	STABLE: X	UNSTABLE:
POLYMERIZATION:	WILL NOT OCCUR: X	WILL OCCUR:

CONDITIONS TO AVOID: High heat

INCOMPATIBILITY (MATERIALS TO AVOID): Alkali will inactivate product

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: N.E.

SECTION 6 - HEALTH HAZARD DATA and FIRST AID INFORMATION

	YES	NO	N.E.	N.A.	NTP	IARC	OSHA	OTHER
MUTAGENIC AFFECTS:		X						
TERATOGENIC AFFECTS:		X						
REPRODUCTIVE TOXIN:		X						
CARCINOGENICITY:		X						
SENSITIZER:		X						

ROUTES OF ENTRY: INHALATION SKIN X INGESTION X

HEALTH HAZARD: (ACUTE AND CHRONIC): Acidic solution (pH=1.90), care should be taken to avoid contact with skin or eyes.

SIGNS AND SYMPTOMS OF OVEREXPOSURE: N.E.

CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: N.E.

SECTION 9- PREPARATION INFORMATION

This data is supplied to comply with OSHA Hazard Communication Standard 29 CFR 1910,1200 and W.H.M.I.S. CPR

PREPARED BY: T. Joritz
Director Regulatory Affairs

Date: 1 November 97

N.A. = NOT APPLICABLE
N.E. = NOT ESTABLISHED

The information herein is given in good faith but no warranty expressed or implied is made.

FIRE 1	TOXICITY 2	NFPA REACTIVITY 0	SPECIAL ACID
--------	------------	----------------------	--------------

MATERIAL SAFETY DATA SHEET

SECTION 1 - SOURCE/IDENTITY/USE INFORMATION

MANUFACTURER

GC AMERICA INC.

3737 West 127th St.

Alsip, Illinois, 60803

Telephone: 708-597-0900

Hours: Mon.- Fri. 8:00 am. - 5:00 pm. C.S.T.

Transportation Emergency Telephone No. 800-424-9300

SUPPLIER

COMMON NAME: FUJI II POWDER
FUJI II CAPSULES POWDER

Chemical Name: N.A.

PRODUCT USE: Dental composite filling material - powder component

The following information is provided with regard to the toxicity and hazards of the pure components present in this portion of the unmixed powder/liquid system.

SECTION 2 - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

COMPONENT AND C.A.S.	EXPOSURE LIMITS	LD50/LC50	%
Polyacrylic acid (not listed)	TWA=10ppm (ACGIH)	LD50 = 2500mg/kg (oral rat) LC50 = N.E.	3-5
Aluminosilicate glass (not listed)	TLV=10mg/m ³ PEL=15mg/m ³ (ACGIH)	N.E.	90-95

SECTION 3 - PHYSICAL/CHEMICAL PROPERTIES

BOILING POINT: N.E. SPECIFIC GRAVITY (H₂O = 1): 2.56
 VAPOR PRESSURE: N.A. MELTING POINT: 1350°C
 VAPOR DENSITY: N.A. EVAPORATION RATE: N.A.
 SOLUBILITY IN WATER: Insoluble ODOR THRESHOLD: N.E.
 COEFFICIENT OF OIL/WATER DISTRIBUTION: N.E.

APPEARANCE AND ODOR: Very fine white powder

SECTION 4 - FIRE AND EXPLOSION DATA

FLASH POINT: Not flammable FLAMMABLE LIMITS: N.A.

EXTINGUISHING MEDIA: Alcohol foam

SPECIAL FIRE FIGHTING PROCEDURES: Full protective clothing and self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None

HAZARDOUS COMBUSTION PRODUCTS: Emits Acrid smoke when heated above 101°C.

SECTION 5 - REACTIVITY DATA

STABILITY:	STABLE: X	UNSTABLE:
POLYMERIZATION:	WILL NOT OCCUR: X	WILL OCCUR:

CONDITIONS TO AVOID: High heat

INCOMPATIBILITY (MATERIALS TO AVOID): Alkali will inactivate product

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: N.E.

SECTION 6 - HEALTH HAZARD DATA and FIRST AID INFORMATION

	YES	NO	N.E.	N.A.	NTP	IARC	OSHA	OTHER
MUTAGENIC AFFECTS:		X						
TERATOGENIC AFFECTS:		X						
REPRODUCTIVE TOXIN:		X						
CARCINOGENICITY:	X						X (Group 2A)	
SENSITIZER:		X						

ROUTES OF ENTRY: INHALATION X SKIN X INGESTION X

HEALTH HAZARD: (ACUTE AND CHRONIC): Contains silica glass, which is considered a hazard by inhalation. IARC has classified it as a probable carcinogenic for humans. Dusts of silica glass is also a known cause of silicosis, a non-cancerous lung disease.

SIGNS AND SYMPTOMS OF OVEREXPOSURE: Irritation and soreness in throat and nose.

CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: May aggravate preexisting upper respiratory and lung disease.

SECTION 6 - HEALTH HAZARD DATA and FIRST AID INFORMATION - continued

EMERGENCY FIRST AID PROCEDURES:

INGESTION: Do not induce vomiting - give large volumes of water. Seek medical attention.

SKIN: Wash with soap and water. If irritation develops seek medical attention.

EYES: Flush with water for 15 minutes. If irritation develops seek medical attention.

INHALATION: Remove to fresh air, drink water to clear throat and blow nose to evacuate dust.

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

IN CASE OF RELEASE OR SPILL: Avoid generating dusts during cleanup. If an excessive amount of dust is generated use a filter equipped vacuum and MSHA/NIOSH approved mask.

WASTE DISPOSAL METHOD: In accordance with local, state, and federal regulations.

STORAGE, HANDLING, AND SPECIAL PRECAUTIONS: Store at normal room temperatures and humidity.

SECTION 8 - CONTROL MEASURES

RESPIRATORY PROTECTION: Minimize exposure to dust in accordance with good hygiene practices. If needed, use MSHA-NIOSH approved respirator.

VENTILATION: None required **LOCAL EXHAUST:** N.A. **MECHANICAL:** YES
SPECIAL: N.A. **OTHER:** N.A.

PROTECTIVE GLOVES: Latex gloves are recommended

EYE PROTECTION: Goggles or full face shield

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Do not spill on clothing.
Eyewash station

WORK/HYGIENIC PRACTICE: Follow safe hygiene practices.

