W9 PTY LTD

A.B.N. 82 001 747 271

Unit 1, 27-29 Salisbury Rd

Hornsby NSW 2077 AUSTRALIA

P: (612) 9987 4224 F: (612) 9476 6629 E: sales@w9.com.au



NATIONAL POISONS INFORMATION 13 11 26

MSDS NO. M002

MATERIAL SAFETY DATA SHEET

I - PRODUCT IDENTIFICATION

COMPANY NAME: Heraeus Kulzer, Inc.

ADDRESS: 4315 S. Lafayette Tel No: (574) 291-0661

South Bend, Indiana 46614 Nights: Chemtrec 800-424-9300

PRODUCT NAME: Modern Materials – Modern Pink, Shur Wax X-Hard, Shur Wax, Utility Wax, Boxing Wax Yellow Bite Wax, Periphery, CoprWax, Yellow Check Bite Wafers, Bite Block Hard, Bite Block Soft, Red

Baseplate, Orthodontic Tray Wax, Prepon, Thin-Ex, Lab Wax

PRODUCT NO(S): 93112, 93152, 93252, 93212, 93312, 93412, 93452, 93513, 93553, 93552, 95492, 95892, 95992, 93712, 94193, 94293, 94191, 94291, 94493, 94593, 94491, 94591, 94693, 94793,

95094, 95194, 93614, 93654, 92178, 92189, 94850, 91164

Synonyms: Paraffin Wax & Natural Occurring Wax

II - HAZARDOUS INGREDIENTS OF MIXTURES

MATERIAL: CAS# | HAZARD | TLV | PEL

None

III - PHYSICAL DATA (ND = Not Determined)

Vapor Pressure, mm Hg:None|Vapor Density (Air =1):NoneEvaporation Rate (ether=1):None|% Volatile by volume:NoneSolubility in H₂O:None|pH: 7.4 (10% Solution)

Boiling Point: NA |Appearance: Wax of various colors and shapes

Specific Gravity (H₂O=1): 0.90 |Odor: Odorless or slight spearmint flavor

IV - FIRE AND EXPLOSION

Flash Point: 400°F Min. COC | Flammable Limits: Not available

Extinguishing Media: Foam, dry chemical, water, CO₂, sand.

Special Fire Fighting Procedures: Do not use water. Self contained breathing apparatus to protect against

smoke inhalation.

Unusual Fire and Explosion Hazards: None.

V - REACTIVITY DATA

Stability: Unstable [] Conditions to avoid: Contact with strong acids.

Stable [X]

W9 PTY LTD

A.B.N. 82 001 747 271

Unit 1, 27-29 Salisbury Rd

Hornsby NSW 2077 AUSTRALIA

P: (612) 9987 4224 F: (612) 9476 6629 E: sales@w9.com.au



NATIONAL POISONS INFORMATION 13 11 26

Incompatibility (Materials to Avoid): None

Hazardous Polymerization: May Occur [] Conditions to avoid: None Will Not Occur [X]

Page 1 of 2 Form MD.500 (5/92)

M002

MODERN MATERIALS WAX PRODUCTS

VI. HEALTH HAZARDS

OSHA Permissible Exposure Limit: None

ACGIH Threshold Exposure Limit: 2 mg/m³ for paraffin wax fumes

Other Exposure Limit Used: None
A. Acute Overexposure: None
B. Chronic, Other: None

Medical conditions generally aggravated by exposure: None

Hygienic Practices: None

Primary Route(s) of Exposure: Skin contact.

Chemical Listed As Carcinogen or potential carcinogen: Not listed

VII - EMERGENCY AND FIRST AID PROCEDURES

Skin: If molten wax contacts skin treat as minor burn.

Ingestion: Consult a physician.

VIII - SPILL OR LEAK PROCEDURES

Spill Management: NA

Waste Disposal Methods: This material can be disposed of as normal solid waste.

IX - PROTECTION INFORMATION/CONTROL MEASURES

Respiratory: None required Eye Protection: None required Gloves: None required

Other Clothing and Equipment: None

Ventilation: None

W9 PTY LTD

A.B.N. 82 001 747 271

Unit 1, 27-29 Salisbury Rd

Hornsby NSW 2077 AUSTRALIA

P: (612) 9987 4224 F: (612) 9476 6629 E: sales@w9.com.au



NATIONAL POISONS INFORMATION 13 11 26

X - SPECIAL PRECAUTIONS

Precautions to be taken in Handling and Storing: Store in cool temperature

CoprWax contains copper which is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right to Know Act of 1986 and of 40CFR 372.

XI - ADDITIONAL INFORMATION

When heating wax, paraffin wax fumes may be present. TWA 2 mg/m³

Date: June 8, 2000

Supersedes MSDS Dated: November 24, 1997

The opinions expressed herein are those of qualified individuals within Heraeus Kulzer, Inc. We believe that the information contained herein is current as of the date of this Material Safety Data Sheet. Since the use of this information and these opinions and the conditions of use of the product are not within the control of Heraeus Kulzer, Inc., it is the user's obligation to determine the conditions of safe use of the product.

Page 2 of 2